


# TECNI®

## Galvanised Steel Cable 19x7 (Very Flexible/Low rotation)

**Construction:** 19x7  
**Tensile:** 1960 N/mm<sup>2</sup>  
**Core:** WSC (Wire Strand Core)  
**Lay:** Right Hand Ordinary (sZ)  
**Material:** Galvanised Steel 1960N/mm<sup>2</sup>  
**Standard:** BS EN 12385-4:2002+A1:2008 Steel wire ropes  
**Factor of Safety:** 5:1  
**Export Commodity Code:** 7312104900



<b>Code</b>	<b>Diameter</b>	<b>Minimum Breaking Load (kg)</b>	<b>Working Load Limit (kg)</b>	<b>Weight per 100m (kg)</b>
506.000.030	3mm	590kgs (5.79kN)	118kgs (1.16kN)	3.5kg
506.000.040	4mm	1045kgs (10.25kN)	209kgs (2.05kN)	5.57kg
506.000.050	5mm	1635kgs (1.71kN)	327kgs (3.21kN)	10.3kg
506.000.060	6mm	2359kgs (23.13kN)	471kgs (4.62kN)	14.5kg

Web: [www.tecni.uk](http://www.tecni.uk)  
Email: [sales@tecni.uk](mailto:sales@tecni.uk)  
Phone: UK (+44) 1278 773510