

## TALURIT™ SPLICING SYSTEM

### Table of sizes for R, RCU, TCU and TCUK ferrules

Ferrule No.				Wire Rope Capacity Diameter (mm)				Die Identification			Required pressure approx. (kN)
				Fill factor (f=0,40-0,50) Fibre Core		Fill factor (f=0,50-0,60) Steel Core		Dies marked	Diameter after pressing		
R	RCU	TCU	TCUK	Min	Max	Min	Max	T	(mm) / Tol.		
1.5	1.5	1.5		0,9	1,0	0,8	0,9	1	3	+0,1	10
				1,1	1,5	1,0	1,4	1,5	3,8	0	20
2	2	2		1,6	2,0	1,5	1,9	2	4	+0,1	30
				2,1	2,6	2,0	2,4	2,5	5	0	45
3	3	3		2,7	3,1	2,5	2,8	3	6		60
				3,2	3,6	2,9	3,3	3,5	7		80
4	4	4		3,7	4,1	3,4	3,8	4	8		100
				4,2	4,6	3,9	4,2	4,5	9		125
5	5	5		4,7	5,1	4,3	4,7	5	10		180
6	6	6		5,2	6,1	4,8	5,6	6	12	+0,3	210
				6,2	6,6	5,7	6,1	6,5	13	0	250
6.5	6.5	6.5		6,2	6,6	5,7	6,1	6,5	13	0	250
				6,7	7,1	6,2	6,6	7	14		320
7	7	7		6,7	7,1	6,2	6,6	7	14		320
				7,2	8,2	6,7	7,5	8	16		410
8	8	8	8	7,2	8,2	6,7	7,5	8	16		410
				8,3	9,0	7,6	8,2	9	18		500
9	9	9	9	8,3	9,0	7,6	8,2	9	18		500
10	10	10	10	9,1	10,1	8,3	9,2	10	20	+0,4	600
				10,2	11,2	9,3	10,2	11	22	0	720
11	11	11	11	10,2	11,2	9,3	10,2	11	22	0	720
				11,3	12,3	10,3	11,2	12	24		850
12	12	12	12	11,3	12,3	10,3	11,2	12	24		850
				12,4	13,4	11,3	12,2	13	26		1 000
13	13	13	13	12,4	13,4	11,3	12,2	13	26		1 000
14	14	14	14	13,5	14,5	12,3	13,2	14	28	+0,5	1 300
				14,6	16,1	13,3	14,7	16	32	0	1 600
16	16	16	16	14,6	16,1	13,3	14,7	16	32	0	1 600
18	18	18	18	16,2	18,2	14,8	16,6	18	36	+0,6	2 000
				18,3	20,2	16,7	18,4	20	40	0	2 400
20	20	20	20	18,3	20,2	16,7	18,4	20	40	0	2 400
				20,3	22,4	18,5	20,4	22	44		2 900
22	22	22	22	20,3	22,4	18,5	20,4	22	44		2 900
24	24	24	24	22,5	24,6	20,5	22,5	24	48	+0,8	3 400
				24,7	26,9	22,6	24,6	26	52	0	3 900
26	26	26	26	24,7	26,9	22,6	24,6	26	52	0	3 900
				27,0	28,6	24,7	26,1	28	56		4 500
28	28	28	28	27,0	28,6	24,7	26,1	28	56		4 500
30	30	30	30	28,7	30,8	26,2	28,1	30	60	+1,0	5 100
				30,9	32,7	28,2	29,9	32	64	0	5 800
32	32	32	32	30,9	32,7	28,2	29,9	32	64	0	5 800

Please note that these instructions are only applicable to products produced and supplied by Talurit AB, Sweden and Gerro GmbH, Germany!



Round ferrule (R)  
(aluminium)



Round copper ferrule (RCU)  
(copper)



Copper ferrule (TCU)  
(copper)

Note: Ferrules made of copper (**RCU**, **TCU** and **TCUK**) have many application areas. One of them being the use together with wire ropes made of stainless steel. This is especially advantageous to avoid galvanic corrosion problems.

**TCU** and **TCUK**: We do not guarantee strength of slings for lifting activities made of Copper turn-back ferrules. A termination performed according to our instructions will normally withstand a tensile strength of 90% of minimum breaking load (MBL) of the wire rope. Verifying tests must be done in order to find out the strength.

Ends stops (**R** and **RCU**) are not allowed to use for lifting applications. The expected strength regarding this end-termination is approximately 50% of the MBL of the wire rope (informative only). Accordingly, verifying tests must be performed to secure the strength of the application.

f = Fill factor, is the ratio between the sum of the nominal metallic cross-sectional areas of all the wires in the rope and the circumscribed area of the rope based on its nominal diameter.

C = Nominal metallic cross-sectional area factor of the rope.

$$C = \frac{f \cdot \pi}{4}$$

**Wire rope:** Above table applies to wire ropes made of stainless steel, bright or galvanized single layer steel wire ropes with round strands and rope grade 1 570 – 1 960. Wire ropes shall conform to EN 12385-4 and 5. The types of rope shall be Ordinary or Lang lay. For higher tensile grade and higher Fill factor, please contact our Technical Department. Note! Stainless steel as a material is not included in the EN standard for wire ropes. Please refer to TALURIT *Ferrule Securing Instruction* for further information.